INDICATOR 320 Weight indicator with extended scale functions

BENEFITS

- Code entry, lb/kg toggle
- Relay for automatic dosing
- Display with backlight
- Internal clock for date/time
- For warehousing, dosing and mixing
- Bluetooth 4.0 for RAVAS WeightsApp



Top quality Advanced functions









INDICATOR 320

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare by push button
- Tare entry by cursor function
- Totaling with sequence number
- Code entry for max. 5-digit codes, by cursor function
- Three data output modes: print, continuous and command/answer
- Ib or kg toggle
- Internal clock (for recording date/time on printout)
- Error messages in display
- Power supply to printer switched on and off by indicator
- Automatic shut-off function, defined by parameter setting
- Low battery indication
- Bluetooth 4.0 for RAVAS WeightsApp

STANDARD SPECIFICATIONS

Display digital

Segments
 LCD, digit height 0.79 inch, backlight,

dual color

Graduation 0.2, 0.5, 1, 2, 5, 10, 20 or 50 lb

(see specifications weighing system)

Housing plastic (ABS)

Bracket steel

Colour red (RAL 3000)Protection class NEMA 4 / IP65

Power supply
 12V (230V for stationary applications)

Power consumption 35 mA

Dimensions exc. bracket: 2.4 x 3 x 7.2 inch





System ISO 9001:2015 ISO 14001:201 ISO 45001:201 www.tuv.com ID 000003720

OPTIONS*

- Printer output to thermal or matrix printer
- Bluetooth or WLAN output
- Relay setpoint switch, for automatic dosing
- RS232 output for cable connection to truck terminal
- Multirange graduation (see specifications weighing system)
- Explosion proof version (Exd)
- RDC, RAVAS Data Collector Software
- RIS, RAVAS Integration Software

