## US-9011SS-EX Intrinsically Safe indicator













- · Easy to setup
- · Easy to use
- Easy replacement parts
- Easy calibration/phone support
- Easy warranty support
- 30 day money back guarantee
- · Lowest price guarantee

CALL NOW: 800-711-2237



## **FEATURES**

- Includes 110V AC Power Adapter
- · Includes Rechargeable Battery
- Includes Mounting Bracket Set-up
- · Gross/Tare/Pre-Set Tare/Zero
- Full Range Zero Setting up to 100%
- Stainless Steel Housing NEMA 4X Rated
- · Weighing Units: LB, KG, G, OZ, or LB:OZ
- · Accumulation, Counting, & Multiple Hold functions
- Overload / Underload alarm
- Date & Time Set-up for Printer / PC
- · Built in Power Saving Mode
- RS-232 port for Printer / PC Communication
- 1" Digits for LCD Digital Display
- Powers up to (6) 350 OHM Load Cells
- Non-NTEP (Not legal for trade)

## **US-9011SS-EX INTRINSICALLY SAFE INDICATOR**

The US-9011SS-EX indicator is Intrinsically Safe for use in dangerous areas. The iSafe indicator has multiple weighing units such as accumulation, counting, gross, tare, zero and multiple hold functions. The built in RS-232 port allows for use with printer, scoreboards, or computer software. Our removable battery pack allows the user the ability to recharge the battery in a safe environment if needed.

## **OPTIONAL ACCESSORIES**

- Thermal Printer
- Label Printer
- Indoor Remote Display 3" Digits
- Indoor Remote Display 5" Digits
- Outdoor Remote Display 6" Digits
- Software
- Indicator Stand (stainless steel)
- · Heavy Duty Indicator Stand
- Certificate of Calibration
- Indicator with 4-20ma Output
- · Indicator with Setpoint / Relay Function