

C A M B R I D G E

DIGITAL WEIGHT INDICATOR MODEL CSW-10AT & CSW-10AT-B



Applications:

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Fork Lift Scales
- General Purpose Weighing
- Remote Display Configuration

Standard Features Include:

- Selectable NTEP 5,000 Division
Non-NTEP 20,000 Division
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- 9 Pin Load Cell Connection
- Simple No-Soldering Load Cell Connection
- Clearly, Visible Center of Zero
Indication on Display
- Lb/Kg Conversion
- Keypad Calibration with Audit Trail
- Weight Totalization
- 1 to 5 Points of Digital Calibration Available
- Span Adjustment at Increasing
or Decreasing Weights
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
 - Printer Output of Gross/Tare/Net
 - Computer Data Output
 - Scoreboard Continuous Output
Alphanumeric or Numeric
- 100-240 VAC, 50/60 Hz Adapter
- Auto Zero Tracking
- Adjustable Motion Detection
- ABS Plastic Dust-Tight Enclosure
with Stainless Steel Swivel Stand

Approvals:



COC # 06-070A1



MEASUREMENT CANADA
AM-5778C



Made in USA

Members:

- THE NATIONAL CONFERENCE ON WEIGHTS AND MEASURES
- THE INTERNATIONAL SOCIETY OF WEIGHING AND MEASUREMENT

C A M B R I D G E

DIGITAL WEIGHT INDICATOR MODEL CSW-10AT & CSW-10AT-B

Model CSW-10AT-B

For portable applications where battery operation is required. Includes all standard CSW-10AT features plus:

- Battery/AC Operation
- Internal Battery Charger
- Lithium-Ion Battery
- Sleep Mode

Optional Features:

Models CSW-10AT & CSW-10AT-B

- 110 VAC Dry Contact Set Point
- Battery Wall Charger
- 12 VDC Accessory Port Power Cable
- Peak Weight Hold
- Ethernet Connection
- Wi-Fi Link to Customers Wireless Hub 802.11 B/G
- Digital Scroll Tare
- Scale Warning System

Contact Cambridge for Additional Options



Cambridge Model CSW-10AT-B

Specifications

Description

| | |
|---------------------------------|---|
| Power - Model CSW-10AT | 100-240 VAC, 50/60 Hz, (12) VDC \pm 10% Output |
| Power - Model CSW-10AT-B | 7.4 VDC 3000 mA ^h * Battery/100-240 VAC Adapter |
| Humidity | 0-90% Non-condensing |
| Enclosure | ABS Plastic |
| Dimensions | 6.5" x 4.3" x 2.5" without Stand, +1 inch with Stand |
| Resolution | NTEP: 5,000 Division, NON-NTEP: 20,000 Division |
| Display | High Efficient, Bright (adjustable) LED—6 Digits— .56" High |
| Input | 0-15mv |
| Temperature | -10° to +40° Celsius |
| Linearity | 0.001% of Full Scale |
| Accuracy | 0.001% of Full Scale |
| Load Cell Supply | 5VDC at 150ma (8 each 350 ohm load cells) |

* (1) 350 OHM Cell - 22hrs / (4) 350 OHM Cell - 20hrs / (8) 350 OHM Cell - 14hrs

Distributed By:

Print Format Samples

Sample Ticket:

Gross(lb): 1200
Tare(lb): 200
Net(lb): 1000

Sample Ticket with Totalization:

Wt# 1 550
Wt# 2 450
Total Wt. 1000 lb



Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship.

Cambridge Scale Works. • P O Box 670 • Honey Brook, PA 19344
(800) 292-7640 • (610) 273-7040 • www.cambridgescale.com

© 2016 Cambridge Scale Works, Inc 12/2016