# US-BT-SS-HP "BENCHTEK STAINLESS STEEL FLOOR SCALE













- · Easy to setup
- · Easy to use
- · Easy replacement parts
- Easy calibration/phone support
- Easy warranty support
- 30 day money back guarantee
- · Lowest price guarantee

CALL NOW: 800-711-2237

#### **INDICATOR FEATURES**

- · Includes US-6011SS LCD Indicator
- · Units: lb, kg, oz, lb:oz, g
- · Stainless Steel Enclosure
- · Counting Pieces Function
- Accumulation Weighing
- Overload /Unload Alarm
- 1" Digits with LCD Backlight
- Gross/Tare/Pre-Set Tare/Zero
- · Built in Rechargeable Battery
- Includes Mounting bracket & hardware
- NTEP Approved Class III (Legal for trade)





## **US-BT1010SS "BENCHTEK"**

USA Measurements "BenchTek" is ideal for customers that need an NTEP approved (Legal for trade) scale. This certification allows a user to buy or sell based on weight. The US-BT is built with a robust 304 graded stainless steel frame, stainless steel digital indicator, 100% overload protection, and has our 5 year warranty. This model scale is great for all wash down applications, outdoor use, and customers that need a reliable, accurate, and durable scale for years to come.

### **PLATFORM FEATURES**

- · Stainless Steel Single Point Load Cell
- · Stainless Steel Platter
- · 100% Overload Protection
- Stainless Steel Column for Indicator
- · Low Profile Design
- Stainless Steel Adjustable Leveling Feet
- · Warranty: 5 Year on Steel Frame
- · Warranty: 2 Year on Electronics
- Easy to Calibrate Digital Indicator
- NTEP Approved Class III (Legal for trade)

# **MODELS**

## US-BT1010SS-HP-6

10"x10" Platform 6 lb x .0002 lb Capacity

## US-BT1818SS-HP-15

10"x10" Platform 15 lb x .0005 lb Capacity

### US-BT1010SS-HP-30

10"x10" Platform 30 lb x .001 lb Capacity

### US-BT1010SS-HP-60

10"x10" Platform 60 lb x .002 lb Capacity





# **OPTIONAL ACCESSORIES**

- · Thermal Printer
- Label Printer
- Indoor Remote Display 3" Digits
- · Indoor Remote Display 5" Digits
- · Outdoor Remote Display 6" Digits
- Software
- · Certificate of Calibration
- · Intrinsically Safe Indicator
- Indicator with 4-20ma Output
- · Indicator with Setpoint / Relay Function





